

FORESTRY MULCHERS FOR SKID STEERS

STC/SSL

Stone crushers for skid steer loaders



80-120 hp



Depth 6 in



STANDARD EQUIPMENT

Hydraulic piston motor 125cc with relief and anticavitation valve	Hydraulic front hood
Safety and anticavitation valve	Working pressure control gauge
Enclosed / anti dust machine body	Additional reinforced side plates
Motor enclosed in the frame	Protection chains
Poly Chain Belt Transmission	Flat pressed welded steel counter-blades
Hydraulic hoses	Adjustable Hardox® counter-blade

OPTIONS

- Diverter valve
- Case drain required

MODEL	STC/SSL 125	STC/SSL 150
Engine (hp)	80-120	90-120
Requirements Flow (gal/min)	29-40	29-40
Pressure (PSI)	3200-5000	3200-5000
Working width (in)	53	63
Overall width (in)	65	75
Weight (lbs)	2403	2668
Rotor diameter (in)	17.7	17.7
Max. working depth (in)	6	6
No. teeth type STCL/3+C/3/SS	26+4	32+4

Data refers to machine as standard set-up. Options may have reflects on weights and dimensions. The technical data in this catalogue may be altered without prior notice.



STCL/3
(standard)



C/3/SS
(side scraper)